



Reyton Fully Synthetic SAE 0W-20

Passenger Car Motor Oil

Product Data Sheet



PRODUCT DESCRIPTION

Reyton Fully Synthetic SAE 0W-20 is an advanced fully synthetic motor oil designed and formulated to ensure ultimate engine protection with reduces fuel consumption. Reyton Fully Synthetic SAE 0W-20 meets or exceeds the requirements of various manufacturers and industry standards which outperforms conventional oils.

BENEFITS

- Preserves and protects engines
- Maintains high power and performance
- Reduces fuel consumption
- Low oil consumption
- Cleaner engine

FEATURES

Reyton Fully Synthetic SAE 0W-20 is a resource conserving, multigrade gasoline engine oil formulated with fully synthetic oils for use in passenger car and light truck engines requiring low viscosity, ILSAC GF-5 or API SN. Specifically tailored viscosity characteristics and effective friction modifier minimize internal engine frictional losses.

APPLICATIONS

- Naturally aspirated and turbocharged gasoline engines in passenger cars where ILSAC GF-5, API SN or earlier ILSAC or API "S" performance categories are specified.
- Light truck gasoline engines where ILSAC GF-5, API SN or earlier ILSAC or API "S" performance categories are specified.

MEETS OR EXCEEDS STANDARDS

- ILSAC GF-5 (licenced)
- API SN, API Resource Conserving (licenced)

TESTS	RESULTS
SAE Grade	0W-20
Viscosity Index	168.122
Kinematic Viscosity	
@40°C, cSt (ASTM D445)	49.275
@100°C, cSt (ASTM D445)	9.083
Phosphorous (ASTM D4951)	0.065
Flash Point, °C (ASTM D92)	210
Pour Point, °C (ASTM D97)	-40
Total Base Number (ASTM D2896)	8
Density, g/ml (ASTM D4052)	0.85