



Reyton Synthetic Based SAE 10W-30 Passenger Car Motor Oil

Product Data Sheet



PRODUCT DESCRIPTION

Reyton Synthetic Based SAE 10W-30 is a synthetic based motor oil designed and formulated to provide superior protection for engine with reduces fuel consumption. Reyton Synthetic Based SAE 10W-30 meets or exceeds the requirements of various manufacturers and industry standards which outperforms conventional oils.

BENEFITS

- Helps minimize oil consumption
- Preserves and protects engines providing maximum engine life
- Superior thermal stability
- Wear protection on engine
- Prevent sludge formation

FEATURES

Reyton Synthetic Based SAE 10W-30 is a multigrade gasoline engine oil formulated with synthetic based oils for use in passenger car requiring SAE 10W-30 viscosity or API SL.

APPLICATIONS

- Naturally aspirated and turbocharged gasoline engines in passenger cars where SAE 10W-30 viscosity API SL or earlier API "S" performance categories are specified.
- Light truck gasoline engines where SAE 10W-30 viscosity, API SL or earlier API "S" performance categories are specified.

MEETS OR EXCEEDS STANDARDS

- API SL/CF

TESTS	RESULTS
SAE Grade	10W-30
Viscosity Index	144.743
Kinematic Viscosity	
@40°C, cSt (ASTM D445)	91
@100°C, cSt (ASTM D445)	13.2
Flash Point, °C (ASTM D92)	215
Pour Point, °C (ASTM D97)	-26
Density, g/ml (ASTM D4052)	0.83