



# Reyton Synthetic Based SAE 20W-50 SL/CF Passenger Car Motor Oil

Product Data Sheet



## PRODUCT DESCRIPTION

Reyton Synthetic Based SAE 20W-50 is a synthetic based motor oil designed and formulated to ensure superior protection for engine with reduces fuel consumption. Reyton Synthetic Based SAE 20W-50 meets or exceeds the requirements of various manufacturers and industry standards which outperforms conventional oils.

## BENEFITS

- Helps minimize engine oil consumption
- Preserves and protects engines
- Superior thermal stability
- Wear protection on engine

## FEATURES

Reyton Synthetic Based SAE 20W-50 is a multigrade engine oil formulated with synthetic based oils for use in passenger car requiring SAE 20W-50 viscosity or API SL/CF.

## APPLICATIONS

- Naturally aspirated and turbocharged gasoline or diesel engines in passenger cars which require SAE 20W-50 viscosity API SL/CF or earlier API "S" and "C" performance categories are specified.
- Light truck gasoline and diesel engines which require SAE 20W-50 viscosity API SL/CF or earlier API "S" and "C" performance categories are specified.
- Heavy duty construction equipment, agricultural equipment, generator sets and heavy duty trucks.

## MEETS OR EXCEEDS STANDARDS

- API SL/CF

TESTS	RESULTS
SAE Grade	20W-50
Viscosity Index	140
Kinematic Viscosity	
@40°C, cSt (ASTM D445)	165
@100°C, cSt (ASTM D445)	19.98
Flash Point, °C (ASTM D92)	225
Pour Point, °C (ASTM D97)	-15
Density, g/ml (ASTM D4052)	0.89

This information was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.