



# Reyton Hydraulic Oil AW 68

## Hydraulic Oil

Product Data Sheet



### PRODUCT DESCRIPTION

Reyton Hydraulic Oil AW 68 is an anti-wear hydraulic oil designed and formulated to be used in equipments where excessive oil consumption and high pressure is experienced. Reyton Hydraulic Oil AW 68 meets or exceeds the requirements of various manufacturers and industry standards which outperforms conventional oils.

### BENEFITS

- High viscosity index
- Excellent protection against rust, wear, oxidation
- High thermal stability
- Maintain high viscosity at high temperature

### FEATURES

Reyton Hydraulic Oil AW 68 is a hydraulic oil which contains highly refined paraffinic, high viscosity index mineral oil incorporating excellent anti-wear, rust, oxidation and water separation properties.

### APPLICATIONS

- Systems requiring high oil make-up additions of an economical general purpose, anti-wear hydraulic oil.
- Ideally suited for use in underground continuous mining equipment (drills, loaders and miners), general machine oiling, chain drives and bearings.

TESTS	RESULTS
ISO Grade	68
Viscosity Index	120.847
Kinematic Viscosity	
@40°C, cSt (ASTM D445)	68.119
@100°C, cSt (ASTM D445)	9.6
Flash Point, °C (ASTM D92)	232
Pour Point, °C (ASTM D97)	-18
Density, g/ml (ASTM D4052)	0.8744