



Reyton Brake Fluid DOT 3

Brake and Clutch Fluid

Product Data Sheet



PRODUCT DESCRIPTION

Reyton Brake Fluid DOT 3 is a brake and clutch fluid designed and formulated to provide excellent lubrication and performance for the braking system and clutch. Reyton Brake Fluid DOT 3 meets or exceeds the requirements of various manufacturers and industry standards which outperforms conventional products.

BENEFITS

- Superior protection for metal surfaces
- Minimizes component wear and leakage
- High thermal and oxidation stability
- Ensures good brake response and good performance during service life

FEATURES

Reyton Brake Fluid DOT 3 is a brake and clutch fluid with high thermal stability recommended for automotive brake and clutch. Reyton Brake Fluid DOT 3 is complies with the SAE J1703 service classification.

APPLICATIONS

- All hydraulically operated vehicle braking systems including drum and disc types for which DOT 3 is specified
- Vehicles with anti-lock (ABS) braking systems
- Hydraulic clutch systems requiring conventional fluids
- For passenger cars, commercial road transport, and motorcycles

MEETS OR EXCEEDS STANDARDS

- SAE J1703

TESTS	RESULTS
Colour	RED
FMVSS Grade	DOT 3
pH	8.5
Viscosity, mm ² /s @ 40°C	1260
mm ² /s @ 100°C	2.22
Equilibrium Reflux Boiling Point, °C	230
Wet Equilibrium Reflux Boiling Point, °C	150