



Reyton Mineral Based HDX 30

Passenger Car Motor Oil

Product Data Sheet



PRODUCT DESCRIPTION

Reyton Mineral Based HDX 30 is a mineral based motor oil designed and formulated to prevent wear on engine components. Reyton Mineral Based HDX 30 meets or exceeds the requirements of various manufacturers and industry standards.

BENEFITS

- Reduces oil consumption
- Minimizes wear on engine

FEATURES

Reyton Mineral Based HDX 30 is a multigrade engine oil formulated with mineral based oils for use in passenger car and heavy duty equipment requiring SAE 30 viscosity or API SF/CF

APPLICATIONS

- Heavy duty construction equipment, agricultural equipment, generator sets and heavy duty trucks.
- Naturally aspirated and turbocharged gasoline or diesel engines in passenger cars where SAE 30 viscosity API SF/CF or earlier API "S" and "C" performance categories are specified.
- Light truck gasoline or diesel engines where SAE 30 viscosity API SF/CF or earlier API "S" and "C" performance categories are specified.

MEETS OR EXCEEDS STANDARDS

- API SF/CF

TESTS	RESULTS
SAE Grade	30
Viscosity Index	100
Kinematic Viscosity	
@40°C, cSt (ASTM D445)	102
@100°C, cSt (ASTM D445)	11.6
Flash Point, °C (ASTM D92)	185
Pour Point, °C (ASTM D97)	-10
Density, g/ml (ASTM D4052)	0.89