



Reyton Mineral Based HDX 40

Passenger Car Motor Oil

Product Data Sheet



PRODUCT DESCRIPTION

Reyton Mineral Based HDX 40 is a mineral based motor oil designed and formulated to prevent wear on engine components. Reyton Mineral Based HDX 40 meets or exceeds the requirements of various manufacturers and industry standards.

BENEFITS

- Reduces oil consumption
- Minimizes wear on engine

FEATURES

Reyton Mineral Based HDX 40 is a multigrade engine oil formulated with synthetic based oils for use in passenger car and heavy duty equipment requiring SAE 40 viscosity or API SF/CF

APPLICATIONS

- Heavy duty construction equipment, agricultural equipment, generator sets and heavy duty trucks.
- Naturally aspirated and turbocharged gasoline or diesel engines in passenger cars where SAE 40 viscosity API SF/CF or earlier API "S" and "C" performance categories are specified.
- Light truck gasoline or diesel engines where SAE 40 viscosity API SF/CF or earlier API "S" and "C" performance categories are specified.

MEETS OR EXCEEDS STANDARDS

- API SF/CF

| TESTS | RESULTS |
|----------------------------|---------|
| SAE Grade | 40 |
| Viscosity Index | 100 |
| Kinematic Viscosity | |
| @40°C, cSt (ASTM D445) | 150 |
| @100°C, cSt (ASTM D445) | 15 |
| Flash Point, °C (ASTM D92) | 185 |
| Pour Point, °C (ASTM D97) | -10 |
| Density, g/ml (ASTM D4052) | 0.89 |